



**KEY SWITCH**

MATERIAL: industrial Silicone Rubber  
 LIFE: Greater than 10 million cycles  
 TRAVEL: 0.055 in.  
 ACTUATION FORCE: 5 oz. (130g)  
 FEEDBACK: Tactile with Mechanical Snap

**HUMIDITY**

100% Humidity Resistant

**POWER**

KEYBOARD: 5V@20ma (from CPU port)  
 HULAPOINT: 5V@10ma (from mouse connection port)

**FLAMMABILITY**

PRINTED CIRCUIT BOARD: 94VO  
 SILICONE OVERLAY: 94HB  
 INTERFACE CABLE: 94VO

**TEMPERATURE**

-40 F to +194 F (-40 C to +90 C)

**SHOCK**

3 X 11 ms pulses of 50g on each of 3 axis

**VIBRATION**

POWER SPECTRAL DENSITY: .04g/HZ  
 FREQUENCY RANGE: 20Hz-2Khz  
 DURATION OF TEST PER AXIS: 3 hours



**MODEL: 102-SLK-PS/2/USB**  
 Specifications / Keypad Layout

Stealth Computer Corporation, 4-530 Rowntree Dairy Road, Woodbridge ON, L4L 8H2

Voice (905) 264-9000 FAX: (905) 264-7440 Email: sales@stealthcomputer.com Website: www.stealthcomputer.com